

High order predictor-corrector schemes using projection-techniques for non linear elastic problems

J.M Cadou^a, M. Potier-Ferry^a, N. Damil^b and B. Braikat^b

^aLaboratoire de Physique et Mécanique des Matériaux
Université de Metz, Ile du Saulcy,
57045 Metz Cedex 01 - FRANCE
cadou@lpmm.univ-metz.fr

^bLaboratoire de Calcul Scientifique en Mécanique
Faculté des Sciences Ben M'Sik,
Université Hassan II - Mohammedia
B.P. 7955 Sidi Othman Casablanca, MAROC
n.damil@univh2m.ac.ma

The most widely used techniques to compute the solution paths of non-linear problems are predictor-corrector algorithms. The principle of these strategies is to follow the branch in a stepwise manner via a succession of linearizations and some iterations to achieve the equilibrium.

Improved high-order predictor corrector algorithms have been recently proposed [1]. The predictors and the correctors are based on homotopy techniques, perturbation techniques and Padé approximants. This extends the Asymptotic Numerical Method, which is an efficient high-order path following technique without corrector [2]. In the proposed high-order correctors [3] [4], one can define a high order Newton algorithm that is efficient, robust and that often converges after a single iteration. Others algorithms denoted as L^* algorithms do not require any triangulation of a large matrix, but they are not as efficient as the previous one.

In this presentation, a reduced basis technique is used to improve the latter method, that is a sort of Newton method on a reduced subspace and a sort of L^* algorithm on the whole space. For instance within the Asymptotic Numerical Method, the vectors issued from the perturbation techniques provide such a subspace. The equation of the problem is split into two equations, by projecting it on the reduced subspace and its orthogonal. The key point is a new class of homotopy transformation. This algorithm is inexpensive, because only an arbitrary matrix L^* and a small matrix have to be inverted.

A few benchmarks emanating from shell buckling analysis are revisited to evaluate the efficiency and the reliability of the proposed algorithms.

References

- [1] H. Lahmam, J.M. Cadou, H. Zahrouni, N. Damil, and M. Potier-Ferry, "High-order predictor-corrector algorithms," *International Journal for Numerical Methods in Engineering*, v. 55, p. 685-704, 2002.
- [2] B. Cochelin, N. Damil, and M. Potier-Ferry, "The asymptotic-numerical method: an efficient perturbation technique for non-linear structural mechanics," *Revue Européenne des Eléments Finis*, v. 3(2), p. 281-297, 1994.
- [3] N. Damil, M. Potier-Ferry, A. Najah, R. Chari, and H. Lahmam, "An iterative process based on homotopy and perturbation techniques," *Communications in Numerical Methods in Engineering*, v. 15, p. 701-708, 1999.
- [4] E. Mallil, H. Lahmam, N. Damil, and M. Potier-Ferry, "An iterative process based on homotopy and perturbation techniques," *Computer Methods in Applied Mechanics and Engineering*, v. 190, p. 1845-1858, 2000.